









# **Full Specifications**



#### **Stepless Electronic Control**

Allows users to make fine power adjustment to produce desired shower temperature.



## **Built-in Residual Current Device (RCD)**

Automatically Power supply cuts off in the event of current leakage.



## **Built-in Flow Sensor**

Cuts off power in the event water flow is less than the rated flow.



## **Double Function Thermostat**

Protects from the risk of scalding in case of overly high temperature.



## **Splash Proof Casing**

Protection against water jet spray from all possible directions.



## **Multi-spray Hand Shower**

Shower Hand Set selection allows users to select preferred shower spray pattern for optimum shower sensation.



## **Built-in DC Silent Pump (Optional)**

Advanced 3-phase brushless DC motor that generate high flow rate & consumes 50% lower electrical power than normal AC motor.



### **Built-in AC Booster Pump (Optional)**

Boosting shower water flow as much as 4.5 times for bathrooms that do not have enough water pressure.



## **Built-in Voltage Surge Protector**

Protects internal electrical circuit from electrical surges and voltage spikes, including those caused by lightning.



#### **UK Technology Heating Element**

Advanced heating technology providing users with instant hot shower water flow, with a guaranteed 5-year warranty.



#### **Unlimited Capacity Hot Water Supply**

Tankless instantaneous water heater technology provides on-demand constant supply of hot water instantly.



## **Triple Function Right Angle Stop Valve**

Smooth 90° water flow control valve with regulator and built-in mesh filter to prevent foreign particles from flowing into the heating element, causing unwanted damages / blockages.



# Distributed by





## CENTON HOME APPLIANCES SDN. BHD. [1289180-P]

21, Jalan Seruling 58, Taman Klang Jaya, 41200 Klang, Selangor, Malaysia



+603 3324 7605 / 7606



+603 3324 7608



support@centon.my



## www.centon.my

## **Technical Data**

## **Heater Electrical Rating**

4.2kW, 220V - 240Vac, 50/60Hz

#### Min. Water Flow Rate

2 litre / min

#### Max. Water Pressure

0.38Mpa (3.8bar / 55psi)

#### Water Temp. Control

**Electronic Control** 

#### **Water Connection**

15mm dia. (1/2" BSP)

#### **Heater Dimensions**

239mm x 392mm x 99mm (H)

### **Heater Weight**

No Pump: 1.7kg, DC Pump: 2.0kg, AC Pump: 2.70kg, Rainshower: + 2.0kg

## DC Pump Electrical Rating (Motor)

Hand Set Models: 36W, 24Vdc Rain Shower Set Models: 55W, 24Vdc **AC Pump Electrical Rating (Motor)** 

120W, 220V-240Vac

## Shower Set




Available with No Pump, or DC Silent Pump



**Box Folds Into Pet House** 

Rain shower box eco-packaging can be upcycled into a house Assembly Guide Included.



# e-Warranty System

Register & check for remaining warranty period ONLINE



Anti-Leak Tank

Heating

Element



DC Silent





PRODUCT LIABILITY



