

Centon



Elegande *series* Instant Water Heater



Export
Excellence
Award
2019

Image for illustration purposes only.
Please consult a certified plumber and obey all building regulations.



SIRIM

Suruhanjaya Tenaga

MADE IN MALAYSIA

Full Specifications



Stepless Electronic Control

Allows users to make fine power adjustment to produce desired shower temperature.



Built-in Residual Current Device (RCD)

Automatically Power supply cuts off in the event of current leakage.



Built-in Flow Sensor

Cuts off power in the event water flow is less than the rated flow.



Double Function Thermostat

Protects from the risk of scalding in case of overly high temperature.



Splash Proof Casing

Protection against water jet spray from all possible directions.



Multi-spray Hand Shower

Shower Hand Set selection allows users to select preferred shower spray pattern for optimum shower sensation.



Built-in Voltage Surge Protector

Protects internal electrical circuit from electrical surges and voltage spikes, including those caused by lightning.



UK Technology Heating Element

Advanced heating technology providing users with instant hot shower water flow, with a guaranteed 5-year warranty.



Unlimited Capacity Hot Water Supply

Tankless instantaneous water heater technology provides on-demand constant supply of hot water instantly.



Triple Function Right Angle Stop Valve

Smooth 90° water flow control valve with regulator and built-in mesh filter to prevent foreign particles from flowing into the heating element, causing unwanted damages / blockages.

PENTAFECTA



DOUBLE FUNCTION THERMOSTAT

Maintains safe water output temperature at all times.



SPLASH PROOF CASING

Protects electrical components against water jet spray.



RCD

Cuts off power supply in the event of current leakage.

selected models only



FLOW SENSOR

Prevents overheating due to insufficient water supply.



NON CONDUCTIVE HOSE

Protects against fatal electrical currents.

selected models only

PENTAFECTA
5-POINT SAFETY SYSTEM BY

Centon

Distributed by

CENTON HOME APPLIANCES SDN. BHD. [1289180-P]

21, Jalan Seruling 58, Taman Klang Jaya,
41200 Klang, Selangor, Malaysia

www.centon.my

support@centonia.my

Technical Data

Heater Electrical Rating

3kW - 8kW, 220-240Vac, 50/60Hz

Min. Water Flow Rate

2 litre / min

Max. Water Pressure

0.38MPa (3.8bar/55psi)

Water Temp. Control

Electronic Control

Water Connection

15mm dia. (1/2" BSP)

Heater Dimensions

326mm x 209mm x 91mm (H)

Heater Weight

1.50kg

Shower Set

Hand Shower



e-Warranty System

Register & check for remaining warranty period ONLINE

10
YEARS

Anti-Leak Tank

5
YEARS

Heating Element

5
YEARS

DC Silent Pump

1
YEAR

Other Electrical & Electronic Parts



FIND IT
ONLINE
AT

Centon
-my

[f](https://www.facebook.com/centonmy) [i](https://www.instagram.com/centonmy) /centonmy