

Centon



NEW



Faucet Diverter


Innov

IV321 Instant Water Heater

SERIES



Export
Excellence
Award
2019



Shower Rail
or Rainshower



Image for illustration purposes only.
Please consult a certified plumber and obey all building regulations.

Full Specifications



Stepless Electronic Control

Allows users to make fine power adjustment to produce desired shower temperature.



Built-in Residual Current Device (RCD)

Automatically Power supply cuts off in the event of current leakage.



Built-in Flow Sensor

Cuts off power in the event water flow is less than the rated flow.



Double Function Thermostat

Protects from the risk of scalding in case of overly high temperature.



Splash Proof Casing

Protection against water jet spray from all possible directions.



Multi-spray Hand Shower

Shower Hand Set selection allows users to select preferred shower spray pattern for optimum shower sensation.



Built-in Voltage Surge Protector

Protects internal electrical circuit from electrical surges and voltage spikes, including those caused by lightning.



UK Technology Heating Element

Advanced heating technology providing users with instant hot shower water flow.



Unlimited Capacity Hot Water Supply

Tankless instantaneous water heater technology provides on-demand constant supply of hot water instantly.



Triple Function Right Angle Stop Valve

Smooth 90° water flow control valve with regulator and built-in mesh filter to prevent foreign particles from flowing into the heating element, causing unwanted damages / blockages.



DOUBLE FUNCTION THERMOSTAT

Maintains safe water output temperature at all times.



SPLASH PROOF CASING

Protects electrical components against water jet spray.



RCD

Cuts off power supply in the event of current leakage.

selected models only



FLOW SENSOR

Prevents overheating due to insufficient water supply.



NON CONDUCTIVE

Protects against fatal electrical currents.

PENTAFECTA Centon
5-POINT SAFETY SYSTEM BY

Distributed by

CENTON HOME APPLIANCES SDN. BHD. [1289180-P]

21, Jalan Seruling 58, Taman Klang Jaya,
41200 Klang, Selangor, Malaysia

www.centon.my

support@centonia.my

Technical Data

Heater Electrical Rating

4.2kW, 220-240Vac, 50/60Hz

Min. Water Flow Rate

2 litre / min

Max. Water Pressure

0.38Mpa (3.8bar / 55psi)

Water Temp. Control

Electronic Control

Water Connection

15mm dia. (1/2" BSP)

Heater Dimensions

219mm(W) x 322mm(L) x 90mm (H)

Heater Weight

1.5kg

Shower Set

White

Black



e-Warranty System

Register for **+1 YEAR** warranty & check for remaining warranty period ONLINE.

10 YEARS

+1 YEAR Anti-Leak Tank

5 YEARS

+1 YEAR Heating Element

1 YEAR

+1 YEAR Other Electrical & Electronic Parts

PRODUCT LIABILITY INSURANCE

RM1,000,000.00

FIND IT ONLINE AT

Centon.my

[f](https://www.facebook.com/centonmy) [i](https://www.instagram.com/centonmy) /centonmy