

INSTANT WATER HEATER













Full Specifications



Stepless Electronic Control

Allows users to make fine power adjustment to produce desired shower temperature.



Built-in Residual Current Device (RCD)

Automatically Power supply cuts off in the event of current leakage.



Built-in Flow Sensor

Cuts off power in the event water flow is less than the rated flow.



Double Function Thermostat

Protects from the risk of scalding in case of overly high temperature.



Splash Proof Casing

Protection against water jet spray from all possible directions.



Multi-spray Hand Shower

Shower Hand Set selection allows users to select preferred shower spray pattern for optimum shower sensation.



Built-in DC Silent Pump (Optional)

Advanced 3-phase brushless DC motor that generate high flow rate & consumes 50% lower electrical power than normal AC motor.



Built-in AC Booster Pump (Optional)

Boosting shower water flow as much as 4.5 times for bathrooms that do not have enough water pressure.



Built-in Voltage Surge Protector

Protects internal electrical circuit from electrical surges and voltage spikes, including those caused by lightning.



UK Technology Heating Element

Advanced heating technology providing users with instant hot shower water flow, with a guaranteed 5-year warranty.



Unlimited Capacity Hot Water Supply

Tankless instantaneous water heater technology provides on-demand constant supply of hot water instantly.



Triple Function Right Angle Stop Valve

Smooth 90° water flow control valve with regulator and built-in mesh filter to prevent foreign particles from flowing into the heating element, causing unwanted damages / blockages.



Distributed by

CENTON HOME APPLIANCES SDN. BHD. [1289180-P]

21, Jalan Seruling 58, Taman Klang Jaya, 41200 Klang, Selangor, Malaysia





support@centonia.my

Technical Data

Heater Electrical Rating

4.2kW, 220V - 240Vac, 50/60Hz

Min. Water Flow Rate

2 litre / min

Max. Water Pressure

0.38Mpa (3.8bar / 55psi)

Water Temp. Control

Electronic Control

Water Connection

15mm dia. (1/2" BSP)

Heater Dimensions

241mm x 386mm x 99mm (H)

Heater Weight

No Pump: 1.5kg, AC Pump: 2.5kg, DC Pump: 2.1kg, Rainshower: +1.9kg

AC Pump Elelctrical Rating (Motor)

120W. 220V-240Vac

DC Pump Electrical Rating (Motor)

36W, 24Vdc

Shower Set

Choice of Rain Shower or Hand Shower



e-Warranty System

Register & check for remaining warranty period ONLINE



Anti-Leak Tank



Heating Element



DC Silent Pump



Other Electrical & **Electronic Parts**

LIABILITY



